



NOTES:
 1- USE JST CONNECTOR OR EQUIVALENT: VHR-5N WITH JST CRIMP TERMINAL OR EQUIVALENT: SVH-4IT-PI.1.

- 2- PIN 1 - GROUND - GREEN WITH YELLOW
- PIN 3 - AC NEUTRAL - LIGHT BLUE
- PIN 5 - AC LINE - DARK BROWN

3- CABLE: UL RATED, SJT, 75°C, 18X3 RATING: 1250W, 10A-125V, BLACK

4- WIRES MUST BE STRIPPED-AND-RETAINED

5- ALL PARTS MUST BE UL RECOGNIZED AND CSA APPROVED

6- CABLE MANUFACTURER MUST FOLLOW CONNECTOR MANUFACTURER'S CRIMP GUIDELINES.

7- ALL PARTS/COMPONENTS MUST BE FREE OF DAMAGES, CUTS.

TOLERANCES:

Unless otherwise specified:
 All dimensions in inches
 .XX +/- .01
 .XXX +/- .005
 Angles +/- 1

THIS DRAWING IS THE PROPERTY OF SYNQOR INC.
 It is not to be reproduced or copied, in whole or in part, or used for furnishing information to others, or for any purpose detrimental to the interests of SynQor. The information shown herein may be protected by patents owned or controlled by SynQor.



155 Swanson Road
 Boxborough, MA 01719

**Input mating cable with
 pre-stripped wire ends (36" long)
 PN # AQ-CBL-INPUT1C**