



MPPS MILITARY FIELD-GRADE

MPPS-4000

3-Phase Military AC-DC Programmable Power Supply

3-Phase, 85-265 Vrms_{L-L} Input Voltage	47-800 Hz Input Frequency	0-80 V Regulated Programmable Output Voltages	4000 W Continuous Output Power
---	--------------------------------------	--	---

Sealed Construction, Ultra low Weight, Compact Size



DESIGNED & MANUFACTURED IN USA

SynQor's Military AC-DC Power Supply units are designed for the extreme environmental and demanding electrical conditions of Military/Aerospace applications. SynQor's MPPS incorporates field proven high efficiency designs and rugged packaging technologies. This MPPS will accept a 3-Phase input with a wide range of input voltage and frequency values while delivering a well-conditioned continuous 4000 W, DC regulated output to the load. The output voltage and output current limit can be adjusted on the fly via RS-232 or web interface. Current sharing allows multiple units to be used in parallel. The MPPS-4000 Power Supply is designed and manufactured in SynQor's USA headquarters and manufacturing facilities to comply with a wide range of military standards.

Combine Up to Eight Units for Higher Power

MPPS Product Features

- Sealed, weather-proof, shock-proof construction
- 4000W output power
- Adjustable output voltage and output current limit
- Full power operation: -40 °C to +55 °C
- 3-Phase AC Input: 85-265 Vrms_{L-L}; 47-800 Hz
- Power factor correction at AC input
- Up to 8 units can be combined for higher power
- User I/O and Configuration signal port
- Synchronized start and stop of multiple units
- Current sharing for paralleled units
- Battle Mode for over-temperature events
- SNMP Network Port
- 1U high rack mount unit (1.73"H x 17.00"W x 20.42"D)
- Low weight: 29.5 lbs.

In-Line Manufacturing Process

- AS9100 and ISO 9001 certified facility
- Full component traceability

Specification Compliance

MPPS units are designed to meet:

- MIL-STD-1399-300B - Interface Shipboard
- MIL-STD-810G - Environmental Engineering
- MIL-STD-461F - Electromagnetic Interference
- MIL-STD-704F - Aircraft Electrical Power
- MIL-STD-1275D - Vehicle Electrical Power

Contents

Technical Specification.....	2
Technical Figures	3
Technical Characteristics.....	4
Block Diagram.....	5
Technical Specification.....	6
Mechanical Diagrams.....	8
Accessory Options.....	9
Ordering Information	10



Technical Specification

PROGRAMMABLE FEATURES				
Model Part Number	Programmable Voltage Range	Programmable Current Range	Voltage Set Point Accuracy (Pout = 0W)	Maximum Output Current (Short Circuit)
28V Default (MPPS-4000-3W28)	0 - 35 V	0 - 150 A	±35 mV typical ±70 mV max.	180 A
48V Default (MPPS-4000-3W48)	0 - 55 V	0 - 120 A	±55 mV typical ±110 mV max.	145 A
72V Default (MPPS-4000-3W72)	0 - 80 V	0 - 78 A	±80 mV typical ±160 mV max.	95 A

Specifications subject to change without notice.

INPUT CHARACTERISTICS	
Operating AC Input	
Voltage	3-Phase, 85-265 Vrms _{L-L} *
Frequency	47-800 Hz
Input Power Factor	>0.98 at 47-65 Hz >0.97 at 400 Hz >0.92 at 800 Hz
Maximum Input Current	27 Arms May be programmed to less via communications port
AC Input Circuit Breaker Rating	30 Arms

*Power Derating vs. Vrms_{L-L} (see Figure 5)

OUTPUT CHARACTERISTICS	
Total Output Power (Continuous**)	
28 V set point (MPPS-4000-3W28)	3750 W
48 V set point (MPPS-4000-3W48)	3750 W, Vin = 115V Vrms _{L-L} 4000 W, Vin = 200 Vrms _{L-L}
72 V set point (MPPS-4000-3W72)	4000 W
**See figures 1-3, 5,6 and the MPPS user guide for derating details	
Output Ripple Voltage (20MHz BW)	
28 V set point (MPPS-4000-3W28)	150 mV pk-pk typ.
48 V set point (MPPS-4000-3W48)	200 mV pk-pk typ.
72 V set point (MPPS-4000-3W72)	250 mV pk-pk typ.
Current Limit Inception	
All Models	110%-120% Rated Current
Hold-up Time	
To -5% Vset, 4000 W	10 ms
Turn-on Delay	
All Output Voltages	2 s max.
Output Voltage Response to Load Transient	
Iout steps from 50-75% at 0.2 A/μs	
28 V set point (MPPS-4000-3W28)	1 V max
48 V set point (MPPS-4000-3W48)	1.5 V max
72 V set point (MPPS-4000-3W72)	2 V max.
Short Circuit Protection	
Constant current source	110-120% Rated Current



Technical Figures




Figure 1: 72V Model Available Output Power vs Output Voltage




Figure 2: 48V Model Available Output Power vs Output Voltage




Figure 3: 28V Model Available Output Power vs Output Voltage




Figure 4: Typical Efficiency vs Output Power. $V_{out} = 72V$




Figure 5: Available Output Power vs Input AC Voltage




Figure 6: Thermal Derating Curve. Output power vs. ambient temperature



Technical Characteristics

ENVIRONMENTAL CHARACTERISTICS MIL-STD-810G

Temperature Methods 501.5, 502.5

Operating Temperature	
Full Rated Power	-40 °C — +55 °C
Reduced Power per Figure 6	-40 °C — +70 °C
Storage Temperature	-40 °C — +70 °C

Altitude Method 500.5

Operating	0 - 18,000 ft
Non-operating	0 - 40,000 ft

Environmental Tests

Shock/Drop	Method 516.6, Procedures 1,4,6
Temperature Shock	Method 503.5, Procedure 1
Vibration	Method 514.6, CAT 5, 7, 8, 9, 24
Fungus	Method 508.6
Salt Fog	Method 509.5
Sand and Dust	Method 510.5, Procedures 1,2
Rain	Method 506.5 Procedure 1
Humidity	Method 507.5 Procedure 2
Mechanical Vibrations of Shipboard Equipment	Method 528 Procedure 1

RELIABILITY CHARACTERISTICS MIL-HDBK-217F

MTBF	190kHrs	MIL-217F Ground Benign, Ta=25 °C
------	---------	----------------------------------

ELECTROMAGNETIC CAPABILITY MIL-STD-461F

CE101	30 Hz - 10 kHz
CE102	10 kHz - 10 MHz
CS101	30 Hz - 150 kHz
CS106	10 kHz - 40 GHz
CS114	10 kHz - 200 MHz
CS116	10 kHz - 100 MHz
RE101	30 Hz - 100 kHz
RE102	10 kHz - 18 GHz
RS101	30 Hz - 100 kHz
RS103	2 MHz - 40 GHz

MECHANICAL CHARACTERISTICS

Standard 1U Chassis

Chassis Size	1.73"(1U)H x 17.00"W x 20.42"D
Case Material	Aluminum
Total Weight	29.5 lbs


Connectors

AC Input Connector	MS3470L18-8PW
DC Output Connector (+)	CGE2E18H5FB-16
DC Output Connector (-)	CGE2E18H5FWB-16
User I/O Ports	HD DB15 Female
Configuration I/O Port	HD DB15 Male
Ethernet Port	Amphenol RJF22N00, Code B

Cooling Exhaust Fans

Sound Pressure Level (SPL)	54 dB(A)
Air Flow	0.67(m3/min) 23.7 CFM

Two fans in system, above specs are for each fan separately.



High Density DB15 Female (15 Pin Connector)

Signal	PIN	Function
TX	2	RS232 DCE Device Transmit
RX	3	RS232 DCE Device Receive
GND	4, 5	Ground reference for all digital inputs and outputs
BATTLE_MODE	6	TTL-Input*, pull "low" to engage Battle Mode (disable internal over-temperature protection), has internal pull-up to +5V.
ACIN_GOOD	7	Open collector* output where "low" indicates AC Input voltage is within range
+5V	8	Vout with minimal current drive usable as a pull-up voltage for open collector output signals. Load must be <35mA
REMOTE_START	12	Drive this line "high" with $\geq 5\text{mA}$ to enable MPPS outputs
SHUTDOWN	13	Drive this line "high" with $\geq 5\text{mA}$ to disable MPPS outputs
OUT_OK	14	Open collector* output where "low" indicates Main DC Output voltage is within range
OVER_TEMP	15	Open collector* output where "low" indicates that the MPPS is at or above its maximum temperature

*With an internal 50k Pull-up Resistor to 5V and ESD Protection Diodes.



Safety & Qualifications - PENDING

UL 60950-1

CAN/CSA C22.2 No.60950-1


EN 60950-1



MPPS-4000-1U UNIT




MPPS-4000-1U UNIT with AC Input





Mechanical Diagrams



Note:

- 1) ALL DIMENSIONS IN INCHES [mm]
- TOLERANCES: X.XXIN +/- 0.02 [0.5]
- X.XXXIN +/- 0.010 [0.25]



SynQor®

MPPS MILITARY
FIELD-GRADE

MPPS-4000

Accessory Options

Rail Kits

Slide Rail Kit	SYN-9002
Fixed Bracket Kit ²	SYN-9038

Power Cables (10' long)

AC Input 30 A (18-8 MIL to NEMA L15-30P)	SYN-9115
AC Input 30 A (18-8 MIL Hardwire)	SYN-9116
DC Output Negative (Hardwire)	SYN-9176
DC Output Positive (Hardwire)	SYN-9177

Rackmount Transit Cases

Transit Case, 3U, Gray, with Casters ²	SYN-9410
Transit Case, 3U, Gray, No Casters ²	SYN-9412

Notes:

- 1: Other Options also available, check the website or contact power@synqor.com for further information.
- 2: Fixed Bracket Kit (SYN-9038) with Transit Case (SYN-9410 or SYN-9412) is required for transit and ruggedized use.



User Communications (I/O) Cables

HD DB15M to DB9F (RS232, 10')	SYN-9301
HD DB15M to DB15M (RS232 and Digital I/O, 10')	SYN-9305
Network SNMP (Sealed RJ45, 10')	SYN-9321

Configuration Cables

HD DB15F to HD DB15F (Synchronized Control of TWO Parallel Units, 3')	SYN-9341
HD DB15F to HD DB15F to HD DB15F (Synchronized Control of THREE Parallel Units, 6')	SYN-9343
HD DB15F to HD DB15F (Synchronized Control of FOUR Parallel Units, 9')	SYN-9344



Optional
Rackmount Transit Case





Ordering Information

Family	Output Power	Height	AC Input Phase #	AC Input Frequency	DC Output Voltage Range	Output Current Range	Network
MPPS	4000: 4000W	1U: 1.73"	3: 3 Phase	W: 47-800Hz	28: 0-35V 48: 0-55V 72: 0-80V	150: 0-150A 120: 0-120A 078: 0-78A	E00: Ethernet/SNMP

For valid part numbers, refer to the website or contact your local sales representative.

Part Numbering Example: MPPS-4000-1U-3W28-150-E00

Contact SynQor for further information and to order:

Phone: 978-849-0600
Toll Free: 888-567-9596
Fax: 978-849-0602
E-mail: power@synqor.com
Web: www.synqor.com
Address: 155 Swanson Road
 Boxborough, MA 01719
 USA

PATENTS

SynQor holds numerous U.S. patents, one or more of which apply to most of its power conversion products. Any that apply to the product(s) listed in this document are identified by markings on the product(s) or on internal components of the product(s) in accordance with U.S. patent laws. SynQor's patents include the following:

6,545,890	6,894,468	6,896,526	6,927,987	7,050,309	7,085,146
7,119,524	7,765,687	7,787,261	8,149,597	8,644,027	

WARRANTY

SynQor offers a 1 year limited warranty. Complete warranty information is listed on our website or is available upon request from SynQor.